

Product data sheet Spirotech

Product name

EVNP Expansion vessel 115L

Product properties

Expansion vessels for systems with buffer tanks, P max. 3 bar / T max. 70°C

- Tested according to the Pressure Equipment Directive 2014/68/EU.
- Max. temperature of the system without/with intermediate vessel: 90/110 °C.
- Max. temperature at the connection point: 70 °C.
- Max. working pressure: 3 bar.

Article number

EVNP115

Product image



Product dimensions

Product data sheet Spirotech

ETIM product data

| | |
|---------------------------------------|---|
| Height | 750 mm |
| Volume | 115 l |
| Colour | Other |
| Diameter | 500 mm |
| Medium temperature (continuous) | 0 - 70 °C |
| Max. operating pressure | 3 bar |
| Connection | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |
| With pressure gauge | No |
| With exchangeable membrane | Yes |
| Nominal diameter expansion connection | 3/4 inch (20) |
| Horizontal positioning | No |
| Suitable for central heating | Yes |
| Vertical positioning | Yes |

| | |
|--------------------------------------|--|
| With legs | Yes |
| Material membrane/bladder | Ethylene-propylene diene monomer rubber (EPDM) |
| With drain | No |
| With safety valve | No |
| With mounting material | No |
| Max. glycol mixture | 60 % |
| Suitable for tap water | No |
| Max. ethanol mixture | 60 % |
| Suitable for solar collector circuit | No |
| Pre-pressure | 1 bar |
| With fixed wall support | No |
| Suitable for cooling | No |

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.

