

Product data sheet Spirotech

Product name

EVU-10 bar Expansion vessel 500L standing

Article number

EVU10-500

Product properties

Safety expansion vessels with replaceable membrane, P max. 10 bar / T max. 70°C.

- Tested according to Pressure Equipment Directive 2014/68/EU
- Max. temperature at connection point: 70 degrees
- Max. operating pressure: 10 bar
- Allowed system medium: water or water/glycol mixture
- Unique 5-year warranty period for vessels $\leq 140L$
- 2-year warranty period for vessels $> 140L$

Product image



Product dimensions

Product data sheet Spirotech

ETIM product data

Height	1561 mm
Volume	500 l
Colour	Other
Medium temperature (continuous)	-10 - 70 °C
Max. operating pressure	10 bar
Connection	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)
With exchangeable membrane	Yes
Horizontal positioning	No
Suitable for central heating	Yes
Vertical positioning	Yes
With legs	Yes

Material membrane/bladder	Ethylene-propylene diene monomer rubber (EPDM)
With vessel manifold	No
With drain	Yes
With mounting material	No
Max. glycol mixture	50 %
Suitable for tap water	No
Suitable for solar collector circuit	Yes
Pre-pressure	4 bar
With fixed wall support	No
Suitable for cooling	Yes

Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.

